North American Cord Set Configurations This information is in accordance with UL817 and CSA C22.2 No. 21-95

	IEC 60320 Connectors										
	0.2A Family		5A mily	6A Family	15A North American Family			20A North American Family			
	Class II	Class I Class II		Class II	Class I Class II			Class I		Class II	
North American NEMA											
Plugs	C1	C5	C7	C9	C13	C15	C15A	C17	C19	C21	C23
(so w 1	X	V	X	X	V	V	V	X	V	V	X
□ 1-15P	V	X	V	V	X	X	X	V	X	X	~
5-20P	X	V	X	X	V	V	V	X	/	V	X
6-15P	X	V	X	X	V	V	V	X	V	V	X
6-20P	X	V	X	X	V	V	V	X	\	~	X
L5-15P	X	V	X	X	V	V	V	X	V	V	X
L5-20P	X	V	X	X	V	V	V	X	V	V	X
L5-30P	X	V	X	X	V	V	V	X	V	V	X
L6-15P	X	V	X	X	V	V	V	X	V	V	X
L6-20P	X	V	X	X	V	~	V	X	V	V	X
L6-30P	X	V	X	X	V	V	V	X	V	V	X

 $[\]checkmark$ Allowed per UL817 and CSA C22.2 No. 21-95 $\,$ Not allowed per UL817 and CSA C22.2 No. 21-95

NOTE: For cable type, size, and material refer to end use product application. A cord set is defined as an assembly consisting of one flexible cable or cord fitted with one plug and one connector.